



ENEOS X PRIME CVT Fluid

CVTF that achieves both comfortable driving and fuel efficiency.

ENEOS X PRIME CVT Fluid is a super high-performance, fully synthetic oil which has been engineered with technological innovation. Crafted with meticulous attention to detail, ENEOS X PRIME CVT Fluid is specifically formulated to meet the exacting standards of Japanese automakers. Renowned for their advanced additives, ENEOS X PRIME CVT Fluid offers superior lubrication, thermal stability, and anti-wear properties, ensuring optimal performance and longevity for CVT systems. With a focus on compatibility with Japanese vehicle designs, using this fluid provides a seamless driving experience, enhancing fuel efficiency and reducing friction for a smoother ride. Trust in the reliability and expertise of Japanese CVT fluid to safeguard your transmission and elevate your driving experience to a new level of precision and efficiency.

SPECIAL FEATURES

(1) Superior Lubrication

ENEOS X Prime CVT Fluid contains special additives that provide excellent lubrication. This lubrication prevents wear and tear on the transmission components, enhancing their durability.

(2) Fuel efficiency and comfortable driving

ENEOS X Prime CVT Fluid allows for seamless and continuous variations in gear ratios, preventing the need for abrupt gear shifts. This smooth power transfer minimizes energy loss during acceleration and deceleration, optimizing fuel efficiency, and provide a smooth and comfortable driving.

(3) Thermal Stability

ENEOS X Prime CVT fluid is specifically designed to withstand the high temperatures generated by the transmission. It remains stable even under extreme heat conditions, ensuring optimal performance.

(4) Excellent wear protection

Design to protect transmission components against wear, rust and corrosion therefore enhance the transmission life.

APPLICATION

ENEOS X PRIME CVT-Fluid can be used for all the Japanese CVT equipped vehicles. We strongly recommend this CVT-Fluid as most luxurious transmission oil to customers who are highly interested in protecting environment and taking great care to their own cars, especially for fuel efficient, low viscosity requirement of CVT transmission units in vehicles from Lexus, Toyota, Honda, Nissan, Mazda, Suzuki, Volkswagen, GM, Ford and other vehicles.

PACK SIZES

1L, 4L

TYPICAL PROPERTIES

Color ASTM	L1.5
Density (15°C), g/cm ³	0.8409
Flash point (COC), °C	220
Pour point, °C	-42.5
Kinematic viscosity (40°C), mm ² /s	27.72
(100°C), mm ² /s	6.5
Viscosity index	201
TBN (HCl method) mg, KOH/g	1.0
TAN, mg KOH/g	1.1
Foaming SEQ.2, ml/ml	20/0

Note: The typical properties may be changed without notice (November 2024)

COMPATIBILITY OF ENEOS CVT FLUID WITH JAPANESE VEHICLES (some examples)

Manufacturer	Name of CVTF	Compatible
Toyota	CVT Fluid TC	Yes
	CVT Fluid FE	Yes
Nissan	Matic Fluid D	Yes
	CVT Fluid NS-1	No
	CVT Fluid NS-2	Yes
	CVT Fluid NS-3	Yes
	CVT Fluid KTF-1	No
Honda	Honda Ultra ATF II ^{*1}	Yes
	Honda Ultra ATF-Z1 ^{*1}	Yes
	Honda Ultra HMMF	Yes
	Honda Ultra HCF-2	Yes
Mitsubishi Motor	Diamond Queen ATF SP III ^{*1}	Yes
	Diamond Queen CVT Fluid 1	Yes
	Diamond Queen CVT Fluid J4	Yes
	Diamond Queen CVT Fluid J4+	Yes
Mazda	CVTF 3320	Yes
SUBARU	E-CVT Fluid	Yes
	SUBARU i-CVT	Yes
	SUBARU i-CVT•FG	Yes

	SUBARU CVT Fluid LINEARTRONIC	Yes
	SUBARU CVT Fluid LINEARTRONIC II	Yes
	SUBARU CVT Fluid LINEARTRONIC III	Yes
	SUBARU High Torque CVT Fluid LINEARTRONIC	<u>No</u>
	SUBARU High Torque CVT Fluid LINEARTRONIC LV	<u>No</u>
Suzuki	SCVT Fluid	Yes
	Suzuki CVT Oil	Yes
	Suzuki CVT Fluid Green1	Yes
	Suzuki CVT Fluid Green1V	Yes
	Suzuki CVT Fluid Green2	Yes
	Suzuki CVT Fluid 3320	Yes
	Suzuki CVT Fluid 4401	Yes
Daihatsu	AMIC CVT Fluid -DC	Yes
	AMIC CVT Fluid -DFE	Yes

(*1) This genuine oil can be used for both AT (automatic transmission) and CVT (continuously variable transmission). Please be sure to check the compatibility data for your specific vehicle.

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.